

PORT NUMBER: 703

UNIVAR USA INC.

PAGE: 001

OS NO: DW25630

MATERIAL SAFETY DATA SHEET

INFRAME UPLOAD DATE: 03/20/03

VERSION: 016

ODUCT: DOWTHERM* SR-1 HEAT TRANSFER FLUID

ORDER NO: 342413

PROD NO : 255881

STEINS INC
3001 - 17TH STREET SO.
P. O. BOX 248

MOORHEAD ,MN 56560

UNIVAR USA INC.

(425)889-3400

100 CARILLON POINT , KIRKLAND

, WA 98033

----- EMERGENCY ASSISTANCE -----

FOR EMERGENCY ASSISTANCE INVOLVING CHEMICALS CALL - CHEMTREC
(800)424-9300

PRODUCT IDENTIFICATION

ODUCT NAME: DOWTHERM* SR-1 HEAT TRANSFER FLUID

OS NUMBER: DW25630

DATE ISSUED: 06/21/02

PERCEDES: 05/23/02

ISSUED BY: 009053

MATERIAL SAFETY DATA SHEET

Dow (hereinafter, and for purposes of this MSDS only, refers to The Dow Chemical Company and to Dow Chemical Canada Inc.) encourages and expects you to read and understand the entire MSDS, as there is important information throughout the document. Dow expects you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

1 IDENTIFICATION

PORT NUMBER: 703 UNIVAR USA INC.
DS NO: DW25630 MATERIAL SAFETY DATA SHEET
INFRAME UPLOAD DATE: 03/20/03

PAGE: 002
VERSION: 016

DUCT: DOWTHERM* SR-1 HEAT TRANSFER FLUID

ORDER NO: 342413
PROD NO: 255881

Product Name DOWTHERM* SR-1 Heat Transfer Fluid, Dyed

2 COMPANY IDENTIFICATION

Dow Chemical Company
Midland, MI 48674

3 EMERGENCY TELEPHONE NUMBER

24-HOUR EMERGENCY TELEPHONE NUMBER: (989)636-4400.
Customer Information Number: 1-800-258-2436.

COMPOSITION INFORMATION

Component	CAS #	Amount (XW/W)
ethylene glycol	107-21-1	> 95 %
potassium hydrogen phosphate	7758-11-4	< 3 %
water	7732-18-5	< 3 %

HAZARDS IDENTIFICATION

1 EMERGENCY OVERVIEW

Appearance
Liquid

Physical State
Liquid

Color
Clear

Hazards of product

IRRMFUL OR FATAL IF SWALLOWED.
MAY CAUSE RESPIRATORY TRACT IRRITATION.

2 POTENTIAL HEALTH EFFECTS

Effects of Single Acute Overexposure

Inhalation
At room temperature, exposure to vapor is minimal due to low volatility. With good ventilation, single exposure is not expected to cause adverse effects. If material is heated or areas are poorly ventilated, vapor/mist may

DDUCT: DOWTHERM* SR-1 HEAT TRANSFER FLUID

ORDER NO: 342413

PROD NO : 255881

accumulate and cause respiratory irritation and symptoms such as headache & nausea.

Eye Contact

Eye contact may cause slight temporary eye irritation. Corneal injury is unlikely. Vapor mist may cause eye irritation.

Skin Contact

Skin contact is essentially nonirritating to skin. Prolonged contact may cause slight skin irritation with local redness. May cause more severe irritation if skin is abraded (scratched or cut).

Inhalation

Prolonged skin contact is unlikely to result in absorption of harmful amounts. Repeated skin exposure to large quantities may result in the absorption of harmful amounts. Massive contact with damaged skin or of material sufficiently hot to burn skin may result in absorption of potentially lethal amounts.

Ingestion

Oral toxicity is expected to be moderate in humans due to ethylene glycol even though tests with animals show a lower degree of toxicity. Excessive exposure may cause central nervous system effects, cardiopulmonary effects (metabolic acidosis), and kidney failure. Swallowing may result in severe effects, even death. The lethal dose in adult humans for ethylene glycol is approximately 3 ounces (100 ml) (1/3 cup). In humans, expected to be moderately toxic if swallowed even though oral toxicity was low when tested on animals. May cause nausea or vomiting. May cause abdominal discomfort or diarrhea.

Chronic, Prolonged or Repeated Overexposure

Effects of Repeated Overexposure Repeated excessive exposure may cause irritation of the upper respiratory tract. In humans, effects have been reported on the following organs: Central nervous system. Observations in humans include: Nystagmus (involuntary eye movement). In animals, effects have been reported on the following organs: Kidney, liver. Based on animal studies, ingestion of very large amounts of ethylene glycol appears to be the major and possibly only route of exposure to produce birth defects. Exposures by inhalation or skin contact, the primary routes of occupational exposure, had minimal effect on the fetus, in animal studies. Ingestion of large amounts of ethylene glycol has been shown to interfere with reproduction in animals.

Other Effects of Overexposure No information available.

ODUCT: DOWTHERM* SR-1 HEAT TRANSFER FLUID

ORDER NO: 342413

PROD NO : 255881

Section 11 for toxicological information and additional information
out potential health effects.

3 POTENTIAL ENVIRONMENTAL EFFECTS

Section 12 for Ecological Information.

FIRST AID PROCEDURES

1 INHALATION

Move person to fresh air; if effects occur, consult a physician.

2 EYE CONTACT

Flush eyes thoroughly with water for several minutes. Remove contact lenses
after the initial 1-2 minutes and continue flushing for several additional
minutes. If effects occur, consult a physician, preferably an
ophthalmologist.

3 SKIN CONTACT

Immediately flush skin with water while removing contaminated clothing and
shoes. Get medical attention if symptoms occur. Wash clothing before reuse.
Discard contaminated articles including leather items such as shoes.

4 SWALLOWING

Do not induce vomiting. Seek medical attention immediately. If person is
fully conscious give 1 cup or 8 ounces (240 ml) of water. If medical advice
is delayed and if an adult has swallowed several ounces of chemical, then
give 3-4 ounces (1/3-1/2 Cup) (90-120 ml) of hard liquor such as 80 proof
whiskey. For children, give proportionally less liquor at a dose of 0.3
ounces (1 1/2 tsp) (8 ml) liquor for each 10 pounds of body weight, or 2
ml per kg body weight (e.g., 1.2 ounce (2 1/3 Tbsp) for a 40 pound child or
12 ml for an 18 kg child).

5 NOTES TO PHYSICIAN

If several ounces of EG have been ingested, early administration of ethanol
may counter the toxic effects (metabolic acidosis, renal damage). Consider
hemodialysis or peritoneal dialysis & thiamine 100 mg plus pyridoxine 50 mg
every 6 hr. If ethanol is used, a therapeutically effective blood
alcohol concentration in the range of 100 - 150 mg/dl may be achieved by a rapid
loading dose followed by a continuous intravenous infusion. Consult standard
literature for details of treatment. 4-Methyl pyrazole (Antizol(r)) is an
effective blocker of alcohol dehydrogenase and should be used in the
treatment of ethylene glycol, di- or triethylene glycol, ethylene glycol
methyl ether, or methanol intoxication if available. Fomepizole protocol
Trent, J. et al., New England Journal of Medicine, Feb. 8, 2001, 344:6,
424-9); loading dose 15 mg/kg IV, follow by bolus dose of 10 mg/kg every
12 hours; after 48 hours, increase bolus dose to 15 mg/kg every 12 hours.
Continue fomepizole until serum methanol, EG, DEG, or TEG are

DDUCT: DOWTHERM* SR-1 HEAT TRANSFER FLUID

ORDER NO: 342413

PROD NO : 255881

detectable. The signs and symptoms of poisoning include anion gap metabolic acidosis, CNS depression, renal tubular injury, and possible late age cranial nerve involvement. Respiratory symptoms, including pulmonary edema, may be delayed. Persons receiving significant exposure should be served 24-48 hours for signs of respiratory distress. In severe poisoning, respiratory support with mechanical ventilation and positive end expiratory pressure may be required. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach.

FIRE FIGHTING MEASURES

1 FLAMMABLE PROPERTIES - REFER TO SECTION 9, PHYSICAL AND CHEMICAL PROPERTIES

2 EXTINGUISHING MEDIA

Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Do not use direct water stream. May spread fire. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

3 FIRE FIGHTING PROCEDURES

Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from a protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles; immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Burning liquids may be extinguished by dilution with water. Do not use direct water stream. May spread fire. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage.

4 SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS

Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, pants, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

5 UNUSUAL FIRE AND EXPLOSION HAZARDS

Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids. Liquid mist of this product can burn. Flammable concentrations of vapor can accumulate at temperatures above flash point; see Section 9.

6 HAZARDOUS COMBUSTION PRODUCTS

PORT NUMBER: 703

UNIVAR USA INC.

PAGE: 006

IDS NO: DW25630

MATERIAL SAFETY DATA SHEET

INFRAME UPLOAD DATE: 03/20/03

VERSION: 016

PRODUCT: DOWTHERM* SR-1 HEAT TRANSFER FLUID

ORDER NO: 342413

PROD NO: 255881

During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: carbon monoxide, Carbon dioxide.

ACCIDENTAL RELEASE MEASURES

Steps to be Taken if Material is Released or Spilled:

Small spills: Absorb with materials such as: cat litter, sawdust, vermiculite, Zorb-all(r). Collect in suitable and properly labeled containers. Large spills: Dike area to contain spill. See Section 13, Disposal Considerations for additional information.

Personal Precautions: Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection. Refer to Section 7, Handling for additional precautionary measures.

Environmental Precautions: Prevent from entering into soil, ditches, rivers, waterways and/ or groundwater. See Section 12, Ecological Information.

HANDLING AND STORAGE

1 HANDLING

General Handling

Do not swallow.
Wash thoroughly after handling.
Avoid breathing vapor and mist.
Work with adequate ventilation.
Keep container closed.
See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Ventilation

Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines.

Other Precautions

Leaks of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion.

2 STORAGE

Do not store in opened or unlabeled containers. Do not store in galvanized steel.

EXPOSURE CONTROLS AND PERSONAL PROTECTION

DDUCT: DOWTHERM* SR-1 HEAT TRANSFER FLUID

ORDER NO: 342413

PROD NO : 255881

1 EXPOSURE LIMITS

Component	Exposure Limits	Skin	Form
ethylene glycol	100 mg/m ³ CEILING ACGIH		Aerosol
	100 mg/m ³ CEILING Interim IHG		Aerosol and Vapor

the Exposure Limits Chart above, if there is no specific qualifier (e.g., Aerosol) listed in the Form Column for a particular limit, the stated limit includes all airborne forms of the substance that can be inhaled.

"Yes" in the Skin Column indicates a potential significant contribution to overall exposure by the cutaneous (skin) route, including mucous membranes and the eyes, either by contact with vapors or by direct skin contact with the substance. A "Blank" in the Skin Column indicates that exposure by the cutaneous (skin) route is not a potential significant contributor to overall exposure.

Interim IHGs" are occupational exposure limits set by the original owner of this product prior to the merger with Dow. These limits have not been reviewed per the Dow IHG process, but are utilized during this period of merger integration until Dow can formally adopt or modify.

2 PERSONAL PROTECTION

Respiratory Protection:

Airborne levels should be maintained below the exposure guideline. Under most conditions, no respiratory protection should be needed; however, if material is heated or sprayed, use an approved air-purifying respirator.

Ventilation:

Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines.

Eye Protection:

Use safety glasses.

If exposure causes eye discomfort, use a full-face respirator.

Other Protective Equipment:

When prolonged or frequently repeated contact could occur, use chemically protective clothing resistant to this material. Selection of specific items such as faceshield, gloves, boots, apron, or full-body suit will depend on operation. If hands are cut or scratched, use gloves chemically resistant to this material even for brief exposures. When handling hot material, protect skin from thermal burns as well as from skin absorption.

DUCT: DOWTHERM* SR-1 HEAT TRANSFER FLUID

ORDER NO: 342413
PROD NO : 255881

PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid

Appearance: Pink

Odor: Sweet

Flash Point - Closed Cup: 111 C 232 F Tag Closed Cup ASTM D 56
(Values for Ethylene Glycol)

Flammable Limits In Air:
Lower 3.2 % (V) (for ethylene glycol)
Upper No test data available.

Autoignition Temperature: 398 C 748 F

Vapor Pressure: 2.2 mmHg 20 C

Boiling Point (760 mmHg): 163 C 325 F

Vapor Density (air = 1): > 1.0

Specific Gravity (H2O = 1): 1.1295 60 C / 60 C

Freezing Point: No test data available.

Melting Point: Not applicable (for liquids)

Solubility in Water (by weight): 100 %

Stability: No test data available.

Molecular Wt

9. STABILITY AND REACTIVITY

9.1 STABILITY/INSTABILITY

Normally stable at recommended temperatures and pressures.

Conditions to Avoid: Exposure to elevated temperatures can cause product to decompose. Generation of gas during decomposition can cause pressure in closed systems.

Incompatible Materials: Avoid contact with: Strong acids. Strong bases. Strong oxidizers.

PRODUCT: DOWTHERM* SR-1 HEAT TRANSFER FLUID

ORDER NO: 342413

PROD NO : 255881

Normal Decomposition: Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Aldehydes, Alcohols, Ethers.

2. HAZARDOUS POLYMERIZATION Will not occur.

TOXICOLOGICAL INFORMATION

ROUTE TOXICITY

Oral

Based on information for a similar material:
LD50 = 8200 mg/kg

Dermal

Based on information for a similar material:
LD50 (> 2000) mg/kg

DEVELOPMENTAL TOXICITY

Based on animal studies, ingestion of very large amounts of ethylene glycol appears to be the major and possibly only route of exposure to produce birth defects. Exposures by inhalation or skin contact, the primary routes of occupational exposure, had minimal effect on the fetus, in animal studies.

REPRODUCTIVE TOXICITY

Ingestion of large amounts of ethylene glycol has been shown to interfere with reproduction in animals.

MUTAGENIC TOXICITY AND CARCINOGENICITY

Ethylene glycol did not cause cancer in long-term animal studies.

OS Comp

GENETIC TOXICOLOGY

In Vitro

For the major component: In vitro mutagenicity studies were negative.

In Vivo

For the major component: Animal mutagenicity studies were negative.

SIGNIFICANT DATA WITH POSSIBLE RELEVANCE TO HUMANS

Repeated excessive exposure may cause irritation of the upper respiratory

ODUCT: DOWTHERM* SR-1 HEAT TRANSFER FLUID

ORDER NO: 342413

PROD NO : 255881

act. In humans, effects have been reported on the following organs:
entral nervous system.

servations in humans include:

stagmus (involuntary eye movement).

animals, effects have been reported on the following organs:
dney, liver.

1. ECOLOGICAL INFORMATION

1.1 ENVIRONMENTAL FATE

sed largely or completely on information for: Ethylene glycol. Material
readily biodegradable. Passes OECD test(s) for ready biodegradability.

1.2 ECOTOXICITY

sed largely or completely on information for: Ethylene glycol. Material
practically non-toxic to aquatic organisms on an acute basis
(50/EC50 >100 mg/L in most sensitive species tested).

1.3 FURTHER INFORMATION

sed largely or completely on information for: Ethylene glycol.
concentration potential is low (BCF < 100 or Log Pow < 3). Potential
r mobility in soil is very high (Koc between 0 and 50).

2. DISPOSAL CONSIDERATIONS

2.1 DISPOSAL

NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All
posal practices must be in compliance with all Federal, State/Provincial
d local laws and regulations. Regulations may vary in different
cations. Waste characterizations and compliance with applicable laws are
e responsibility solely of the waste generator. DOW HAS NO CONTROL OVER
IE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR
ING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE
ODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION 2
omposition/ Information On Ingredients). FOR UNUSED & UNCONTAMINATED
ODUCT, the preferred options include sending to a licensed, permitted:
ycler, reclaimer, incinerator or other thermal destruction device.
a service to its customers, Dow can provide names of information
sources to help identify waste management companies and other facilities
ich recycle, reprocess or manage chemicals or plastics, and that manage
ed drums. Telephone Dow's Customer Information Group at 1-800-258-2436
1-989-832-1556 (U.S.), or 1-800-331-6451 (Canada) for further details.

PORT NUMBER: 703

UNIVAR USA INC.

PAGE: 011

JS NO: DW25630

MATERIAL SAFETY DATA SHEET

INFRAME UPLOAD DATE: 03/20/03

VERSION: 016

PRODUCT: DOWTHERM+ SR-1 HEAT TRANSFER FLUID

ORDER NO: 342413

PROD NO : 255881

TRANSPORT INFORMATION

1 U.S. D.O.T.

N-BULK

proper Shipping Name : NOT REGULATED

LK

proper Shipping Name : OTHER REGULATED SUBSTANCES, LIQUID, NOS

chemical Name : CONTAINS ETHYLENE GLYCOL

Hazard Class : 9

Number : NA3082

Packing Group : PG III

Net Quantity : 5,263 LB

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized sales customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

REGULATORY INFORMATION

1.1 FEDERAL/NATIONAL

OSHA HAZARD COMMUNICATION STANDARD

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 TITLE III (EMERGENCY PLANNING AND COMMUNITY RIGHT TO KNOW ACT) SECTION 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act 1986 and 40 CFR Part 372.

Component	CAS #	Amount
Ethylene glycol	107-21-1	> 95.0000 %

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 TITLE III (EMERGENCY

PORT NUMBER: 703

UNIVAR USA INC.

PAGE: 012

DS NO: DW25630

MATERIAL SAFETY DATA SHEET

INFRAME UPLOAD DATE: 03/20/03

VERSION: 016

ODUCT: DOWTHERM* SR-1 HEAT TRANSFER FLUID

ORDER NO: 342413

PROD NO : 255881

ANNING AND COMMUNITY RIGHT TO KNOW ACT) SECTION 302

the best of our knowledge this product does not contain chemicals at levels which require reporting under this statute.

PERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 TITLE III (EMERGENCY ANNING AND COMMUNITY RIGHT TO KNOW ACT) SECTIONS 311 AND 312

Delayed (Chronic) Health Hazard : Yes

Fire Hazard : No

Immediate (Acute) Health Hazard : Yes

Reactive Hazard : No

Sudden Release of Pressure Hazard : No

XIC SUBSTANCES CONTROL ACT (TSCA)

1 component of this product are on the TSCA Inventory or are exempt from CA Inventory requirements.

PA - DOMESTIC SUBSTANCES LIST (OSL)

is product contains one or more substances which are not listed on the Canadian Domestic Substances List (OSL). Contact your Dow representative for more information.

1.2 STATE/LOCAL

PENNSYLVANIA (WORKER AND COMMUNITY RIGHT TO KNOW ACT); PENNSYLVANIA HAZARDOUS SUBSTANCES LIST AND/OR PENNSYLVANIA ENVIRONMENTAL HAZARDOUS SUBSTANCE LIST:

the following product components are cited in the Pennsylvania Hazardous Substance List and/or the Pennsylvania Environmental Substance List, and are present at levels which require reporting.

Component	CAS #	Amount
ethylene glycol	107-21-1	95.0000 %

PENNSYLVANIA (WORKER AND COMMUNITY RIGHT TO KNOW ACT); PENNSYLVANIA SPECIAL HAZARDOUS SUBSTANCES LIST:

the best of our knowledge this product does not contain chemicals at levels which require reporting under this statute.

CALIFORNIA PROPOSITION 65 (SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986)

is product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which

DDUCT: DOWTHERM* SR-1 HEAT TRANSFER FLUID

ORDER NO: 342413

PROD NO : 255881

uld require a warning under the statute.

LIFORNIA SCAQMD RULE 443.1 (SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT RULE 3.1, LABELING OF MATERIALS CONTAINING ORGANIC SOLVENTS)

C : Not determined.

is section provides selected regulatory information on this product including its components. This is not intended to include all regulations. is the responsibility of the user to know and comply with all applicable les, regulations and laws relating to the product being used.

. OTHER INFORMATION

.1 ADDITIONAL INFORMATION

ditional information on this and other Dow products may be obtained by siting our web page at www.dow.com. Additional information on this product y be obtained by calling Dow's Customer Information Group at 1-800-258-2436 (S.) or 1-800-331-6451 (Canada). Ask for a product brochure.

.2 HAZARD RATING SYSTEM

PA

atings for this product are:

- 1
- 1
- 0

hese ratings are part of a specific hazard communication program and should e disregarded where individuals are not trained in the use of this hazard ating system. You should be familiar with the hazard communication programs plicable to your workplace.

.3 RECOMMENDED USES AND RESTRICTIONS

or industrial use.

ow recommends that you use this product in a manner consistent with the isted use. If your intended use is not consistent with Dow's stated use, lease contact Dow's Customer Information Group at 1-800-258-2436 (U.S.) or -800-331-6451 (Canada) for more information.

.4 REVISION

ersion: 1.

evision: 06/21/2002

PORT NUMBER: 703

UNIVAR USA INC.

PAGE: 014

DS NO: DW25630

MATERIAL SAFETY DATA SHEET

INFRAME UPLOAD DATE: 03/20/03

VERSION: 016

DDUCT: DOWTHERM* SR-1 HEAT TRANSFER FLUID

ORDER NO: 342413

PROD NO : 255881

5 LEGEND

cterial/NA Non Acclimated Bacteria
Fire
Health
IG Industrial Hygiene Guideline
A Not available
PA National Fire Protection Association
Oxidizer
Reactivity
Trade secret
L/VOL Volume/Volume
Water Reactive
W Weight/Weight

or (r) Indicates a Trademark of The Dow Chemical Company.

PORT NUMBER: 703

UNIVAR USA INC.

PAGE: 015

IDS NO: DW25630

MATERIAL SAFETY DATA SHEET

INFRAME UPLOAD DATE: 03/20/03

VERSION: 016

PRODUCT: DOWTHERM* SR-1 HEAT TRANSFER FLUID

ORDER NO: 342413

PROD NO : 255881

----- FOR ADDITIONAL INFORMATION -----

CONTACT: MSDS COORDINATOR

UNIVAR USA INC.

DURING BUSINESS HOURS, PACIFIC TIME

(425)889-3400

08/26/04 08:15

PRODUCT: 255881

CUST NO: 155411

ORDER NO: 342413

----- NOTICE -----

***** UNIVAR USA INC("UNIVAR"), EXPRESSLY DISCLAIMS

ALL EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A

PARTICULAR PURPOSE, WITH RESPECT TO THE PRODUCT OR INFORMATION PROVIDED

HEREIN, AND SHALL UNDER NO CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR

CONSEQUENTIAL DAMAGES. **

DO NOT USE INGREDIENT INFORMATION AND/OR PERCENTAGES IN THIS MSDS AS A
PRODUCT SPECIFICATION. FOR PRODUCT SPECIFICATION INFORMATION REFER TO A PRODUCT
SPECIFICATION SHEET AND/OR A CERTIFICATE OF ANALYSIS. THESE CAN BE OBTAINED FROM
OUR LOCAL UNIVAR SALES OFFICE.

ALL INFORMATION APPEARING HEREIN IS BASED UPON DATA OBTAINED FROM THE
MANUFACTURER AND/OR RECOGNIZED TECHNICAL SOURCES. WHILE THE INFORMATION IS
BELIEVED TO BE ACCURATE, UNIVAR MAKES NO REPRESENTATIONS AS TO ITS ACCURACY OR
EFFICIENCY. CONDITIONS OF USE ARE BEYOND UNIVAR'S CONTROL AND THEREFORE USERS
ARE RESPONSIBLE TO VERIFY THIS DATA UNDER THEIR OWN OPERATING CONDITIONS TO
DETERMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR PARTICULAR PURPOSES AND THEY
ASSUME ALL RISKS OF THEIR USE, HANDLING, AND DISPOSAL OF THE PRODUCT, OR FROM
THE PUBLICATION OR USE OF, OR RELIANCE UPON, INFORMATION CONTAINED HEREIN.
THIS INFORMATION RELATES ONLY TO THE PRODUCT DESIGNATED HEREIN, AND DOES NOT
APPLY TO ITS USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY OTHER
PROCESS.

*** END OF MSDS ***

